

TECHNICAL SPECIFICATIONS:

Bitumen Tank	<ul style="list-style-type: none"> - AI - 4000 / AI - 6000 / AI - 8000 - Capacity : 4000 / 6000 / 8000 Liters - Tank Shape : Oval - Insulation : 50 mm Thick glass wool - Temperature Gauge : 0-300 ° C - Main hole : 450 mm diameter - Mounting: Tank mounted on any truck chassis of wheel base 176" / 166"
Spray Bar	<ul style="list-style-type: none"> - Length: 2.4 Mtr. - Length with Extension : 4.20 Mtr. - Control of Spray Bar : Fully circulating of Pre-heated bitumen - Bitumen Spraying Pressure : 0-4 Kg./ cm 2
Bitumen Pump	- 2" x 2" Size positive displacement gear pump with output of 400 Ltr/Min.
Air Compressor	- Standard make 2 Cyl. Air compressor
Burner	- Fuel Consumption : 20 Ltr./Hr.
Engine Fuel Tank	- 50 Ltrs. Capacity
Burner Fuel Tank	- 100 Ltrs. Capacity
Engine	- Standard make air cooled diesel engine

With Atlas's policy of constant upgradation of products, specifications are subject to change without prior notice.

Accessories shown are optional and not a part of standard supply.

•Capacities above 8000 liters are tailor made