

MINI BITUMEN SPRAYER

TECHNICAL SPECIFICATIONS:

Bitumen Tank	<i>Model</i>	<i>AI 3000</i>
	<i>Capacity</i>	<i>3000 liters</i>
	<i>Shape</i>	<i>U Shape</i>
	<i>Insulation</i>	<i>40 mm thick with glass wool</i>
	<i>Temp. Gauze</i>	<i>0-300° C</i>
	<i>Main hole</i>	<i>450 mm in diameter</i>
	<i>Mounting</i>	<i>Self chassis mounted on wheels</i>
Manual hand spraying	<i>Pipe Length</i>	<i>3 meters</i>
	<i>Type of Pipe</i>	<i>S. S. corrugated hose pipe</i>
	<i>Bitumen Spraying Pressure</i>	<i>0-3 Kg./ cm²</i>
Bitumen Pump	<i>1.5" x 1.5" Size positive displacement gear pump with output of 200-300 liters/ min.</i>	
Air Compressor	<i>Standard make Air compressor</i>	
Burner	<i>Fuel consumption 7-8 liters/ hour</i>	
Engine Fuel tank	<i>Capacity 5 liters</i>	
Burner Fuel tank	<i>Capacity 20 liters</i>	
Engine	<i>Standard make air cooled diesel engine</i>	

With Atlas's policy of constant upgradation of products, specifications are subject to change without prior notice.

Accessories shown are optional and not a part of standard supply.